

321.258 Arrangement of lights on official traffic-control signals.

1. Colored lights placed on a vertical official traffic-control signal face shall be arranged from the top to the bottom in the following order when used:

- a. Circular red.
- b. Steady and/or flashing left-turn red arrow.
- c. Steady and/or flashing right-turn red arrow.
- d. Circular yellow.
- e. Circular green.
- f. Straight-through green arrow.
- g. Steady left-turn yellow arrow.
- h. Flashing left-turn yellow arrow.
- i. Left-turn green arrow.
- j. Steady right-turn yellow arrow.
- k. Flashing right-turn yellow arrow.
- l. Right-turn green arrow.

2. Colored lights placed on a horizontal official traffic-control signal face shall be arranged from the left to the right in the following order when used:

- a. Circular red.
- b. Steady and/or flashing left-turn red arrow.
- c. Steady and/or flashing right-turn red arrow.
- d. Circular yellow.
- e. Steady left-turn yellow arrow.
- f. Flashing left-turn yellow arrow.
- g. Left-turn green arrow.
- h. Circular green.
- i. Straight-through green arrow.
- j. Steady right-turn yellow arrow.
- k. Flashing right-turn yellow arrow.
- l. Right-turn green arrow.

[C79, 81, §321.258]

[2014 Acts, ch 1026, §77](#); [2014 Acts, ch 1123, §17](#)

See Code editor's note at the end of Vol VI

Section amended